

CITIZEN

Micro HumanTech

Performance ticket & label printing Compact footprint and metal mechanism



Fanfold or Roll Media

The CL-S400DT can handle fanfold tickets as well as standard roll media for labels or receipts.

Easy Read LCD Panel



The LCD panel allows quick and simple configuration and also flashes red

when an error occurs quickly alerting the operator.

Environmentally friendly

From production and packaging to utilisation and recycling the CL-S400DT fulfills today's demand for green IT products. The integrated ENERGY STAR® power supply is one of the most efficient at managing power consumption.

www.citizen-europe.com

CITIZEN CL-S400DT

LABEL

Applications

- Event Ticketing
- Ticket Bureaux
- Boarding Passes
- Shelf-Edge Tags
- Retail Swing Tags
- Fanfold Labels



Easy Operation and Media Change

Tickets and labels can be stacked behind the printer and easily changed with the Hi-Open™ print mechanism.





Dual Interface With a USB and serial interface on board the CT-S400DT is a future-proof investment. Ethernet and parallel interfaces are available as options.

Specifications

| | |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Technology | Direct Thermal |
| Resolution | 203 dpi (8 dots per mm) |
| Emulations (Languages) | Datamax® I-Class™ & DMX400™, Zebra® ZPL-II®. Cross-Emulation™ automatic detection BASIC interpreter for data stream processing and ticketing emulations |
| Print Speed (maximum) | 6 inches per second (150 mm/s) |
| Print Width (maximum) | 4.10 inches (104.1 mm) |
| Media Width (min to max) | 0.77 inches to 4.65 inches (19.5 mm to 118.0 mm) |
| Media Thickness (min to max) | 0.0025 - 0.01 inches (0.0635 - 0.254 mm) |
| Media Sensor | Fully adjustable with label gap, card notch and black registration mark |
| Media Length (min to max) | 0.25 inches to 32.00 inches (6.35 mm to 812.8 mm) |
| Roll Size (max), Core size | 5 inches (125 mm) diameter with standard holder. Core size: 1 inch (25mm) |
| Standard Interfaces | Serial (RS-232C), USB (version 2.0, full speed) |
| Optional Interfaces | Parallel (IEEE-1284), Ethernet (10/100 BaseT) |
| Case, Mechanism | Hi-Open™ plastic case with safe close. Hi-Lift™ metal mechanism |
| Control Panel | 16x2 LCD with two-colour backlight. 4 buttons and sophisticated menu and configuration system |
| RAM (Standard Memory) | 16.0 MB total, 1.0 Mb available for user |
| Flash (Non-Volatile Memory) | 8.0 MB total, 1.0 Mb available for user |
| Autocutter Option | Guillotine type, Dealer Installable |
| Number of cuts | 300,000 cuts on media 0.06-0.15mm; 100,000 cuts 0.15-0.25mm |
| Windows® drivers and software | Free-of-charge on CD including design software supporting Windows®, XP®, 2003, 2008, Vista™, Windows 7 |
| Size (W x D x H) and Weight | 206 x 149 x 150mm, 2.68 Kgs (excluding roll holder) |
| Printer, Head Warranty | 2 Years for Printer; 30 Kms or 6 months on Print Heads |

CITIZEN CL-S400DT LABEL

Features & Benefits

- Hi-Lift™ mechanism for easy media loading
- Self-contained metal mechanism for durable operation
- Built-in ENERGY STAR® power supply, 220-240V, 50-60Hz
- Both Zebra® and Datamax® emulations as installed as standard
- BASIC interpreter for code conversion and support for other ticketing emulations
- Adjustable media sensors for tags with unusual cut-outs or black marks
- Standard tear-bar for perforated tags or optional autocutter
- Internal USB, Serial, Parallel and Ethernet interface configurations
- Media roll holder or fanfold stacked media
- Optional cutter and peeler

